Product Specifications



2x 10G SFP ports, 24x 2.5G Ethernet ports, Unmanaged Commercial Switch (SR-S25G1226F)

产品概述

The SR-S25G1226F series is an unmanaged switch equipped with 24 auto-negotiating 2.5G RJ45 ports and 2 10G SFP+ fiber ports, specifically designed to meet the networking needs of growing enterprises.
The SR-S25G1226F series offers multiple operating modes for applications such as security surveillance, diskless boot, and wireless networking, delivering excellent network adaptability .

产品特点

Features 24 auto-negotiating 10/100/1000/2500M RJ45 ports and 2 10 Gigabit SFP+ ports.
Compliant with IEEE 802.3/802.3u/802.3ab/802.3bz/802.3x/802.3cb standards
Full-duplex flow control complies with the IEEE 802.3x standard, while half-duplex employs the Backpressure standard.
The port supports auto-negotiation, automatically adjusting the transmission mode and speed.
All ports support wire-speed forwarding.
Plug and play, no configuration required

Hardware Specifications

协议标准	IEEE 802.3/802.3u/802.3ab/802.3bz/802.3x/802.3cb
端口	24 x 10/100/1000/2500Mbps RJ45 ports, 2 x 10 Gigabit fiber ports
指示灯	24 link/act indicators, 24 2.5G rate indicators, 2 10G link/act indicators, power input indicator
网络介质	10Base-T UTP Category 3, 4, 5 cable (maximum 100 meters) 100Base-Tx: UTP Category 5, 5e cable (maximum 100 meters) 1000Base-T: UTP Category 5e, 6 cable (maximum 100 meters) 2.5GBase-T: UTP Category 5e, 6 cable (maximum 100 meters) 10G SFP+: Fiber optic
电源输入	AC100~240V 50/60Hz
尺寸	440*180*44mm
背板带宽	160Gbps
转发速率	119.04Mpps
转发机制	Store-and-Forward
MAC地址表	16K
缓存	12Mbit
环境	Operating Temperature: 0°C to 45°C (0°F to 113°F) Storage Temperature: -40°C to 70°C (-40°F to 158°F) Operating Humidity: 10% to 90% RH, non-condensing Storage Humidity: 5% to 95% RH, non-condensing