Product Specifications



8GE+2G SFP L2+ Managed PoE Switch (SR-SG3210FP)

- Gigabit L2+ managed POE switch.
- 8 10/100/1000Mbps RJ45 and 2G SFP ports.
- 8 POE ports support 802.3af/at
- Support VLAN, ACL, IPV6, SSL, SNMP.
- Support 802.1X certification.
- Support ERPS ring network.
- Support RSTP/MSTP spanning tree.
- Support AI smart POE, automatically detect PD devices, Support PoE Watchdog.

Product Description

SR-SG3210FP from is a layer 2+ managed PoE switch equipped with 8 Gigabit RJ45 ports, 2G SFP fiber ports, and 1 console port. All RJ45 Ports support the 802.3af/at PoE standard, supplying both data and power over 100M.

With abundant layer 2+ management features supported, the SR-SG3210FP is capable of delivering high-throughput via the most demanding applications in network workgroups, while in small networks it can act as a backbone for Gigabit switches and high-speed servers. 2 SFP slots provide greater network flexibility.

The SR-SG3210FP is designed exclusively for the networking needs of growing businesses, with an extensive suite of management and security features available. These devices are cost-effective for small and medium-sized businesses, providing ideal solutions for a variety of network scenarios.

Features

- Supports IEEE 802.3i, 802.3u, 802.3ab, 802.3z, 802.3x , 802.3az, 802.3at, 802.3af.
- 8 POE ports support 802.3af/at, per port can output up to 30W, and 150W total power.
- Provide 8 10/100/1000Mbps RJ45 ports, 2 Gigabit SFP fiber ports.
- Supports MAC address auto-learning and auto-aging.
- Store and forward mode operates.
- LED indicators for monitoring power, link/activity.
- Supports QoS, port mirroring, link aggregation protocol.
- 19 inches full metal iron shell and internal power adapter design, suitable for rack installation

Energy saving and low noise

- Following the IEEE 802.3az (Energy Efficient Ethernet) standard, it greatly reduces the power consumption of the equipment, is green and energy-saving.
- Fully considering the low noise requirements of the user environment, the fanless design is adopted to monitor the temperature in the system in real time, which can effectively reduce noise pollution.

Simple and flexible operation and maintenance management

- Supporting unified management of the entire network configuration and web management can simplify operations and improve deployment reliability.
- Supports power alarm and port status alarm, users can set the alarm mode correspondingto the power supply of the device and the port, which is convenient for user operation and maintenance.
- Supports perfect SNMP management, support YCT, DDM (Digital Diagnostic Monitoring) and other features, quickly detect network faults and inform the difficulty of operation and maintenance.
- It supports the function of sending information to the server. The logs generated by the device are sent to the information server in a unified manner. Through the unified management of logs, it is convenient to locate the fault, and use different notification is realized, which is convenient for monitoring the running status of the equipment and locating faults.

Enhanced protection, safe and controllable

- Supports a variety of security protection mechanisms, provides various DOS-type attack defense technologies such as SYN Flood, Land, ICMP Flood, supports BPDU Filter, BPDU Guard, Root Guard and loopback-logs and illegal edge devices become root nodes, preventing unnecessary topological oscillations.
- In terms of anti-attack measures for the user layer, it supports both port-based and VLAN-based ARP detection and IP Source Guard. The combination of the two can effectively prevent illegal address spoofing such as MAC, IP, and MAC+IP, and can also reduce ARP broadcasts.
- Supports the source MAC address learning restrictions of port-based and VLAN-based, which can effectively limit user source MAC spoofing from exploiting device MAC table entries, causing normal users to fail to learn the MAC table and flooding. Through the DAI function, illegal user access can be prevented from attacking the network through ARP loopholes, which can minimize the intermittent and frequent disconnection of the user's network use, and increase the security and availability of the network.
- Supports custom ACL, more flexible to match the Ethernet header or IP header of the packet according to user requirements. Provides a complete ACL policy, can classify data according to the data of the packet, and use different policies for forwarding.
- It supports standard 802.1X authentication access, and at the same time supports extended 802.1X authentication access, which can effectively prevent IP conflicts and IP cloning, and realize extended and enhanced functions such as static IP address delivery.
- It supports Web Portal authentication access, and can push Web Portal page authentication for access users based on Http and Https two protocols.

Redundant backup, stable and reliable

- The first to support the industry-standard ERPS ring network solution, support single-ring networking mode, <20ms convergence speed, and achieve carrier-class reliability.
- Multi-process MSTP is supported, each process can run different spanning tree protocols, and the number of network sub-rings is increased at the same time. The new access ring can be realized by creating a new MSTP process, which does not affect the original service traffic and reduces network impact.
- Built-in lightning protection technology, service ports provide 4KV lightning protection capability, effectively resist lightning strikes, more adaptable to harsh environments than ordinary switches, and greatly reduce the damage rate of equipment.

VLAN expansion, abundant and diverse

- Supports common QinQ and flexible QinQ technologies, giving users maximum freedom to configure QinQ policies.
- Supports multiple VLAN types such as protocol VLAN, MAC VLAN and Voice VLAN, plays a role in multi-service converged networks.

Hardware Specification

SR-SG3210FP	
Power Supply	AC100~240V 50/60Hz
Standards	IEEE 802.3i,802.3u,802.3ab,802.3z,802.3az,802.3at,802.3af
Ports	8 x 10/100/1000Mbps RJ45 ports, 2 x 1000Mbps SFP fiber ports, 1x Console port
Indicators	Electrical port indication: optical port indicator, power input indicator, system running indicator
Network Media (Cable)	10Base-T: UTP category 3, 4, 5 cable (maximum 100m) 100Base-TX: UTP category 5, 5e cable (maximum 100m) 1000Base-T: UTP category 5e, 6 cable (maximum 100m) 1000Base-X: MMF, SMF
Dimensions	271*181.5*43.6 mm
PoE port	8 802.3af/at standard POE
PoE Pin Assignment	1/2+3,6(-)
PoE power	130W
Total power	150W
Transfer Method	Store-and-Forward
MAC Address Table	8K
Switching Capacity	20Gbps
Packet Forwarding Rate	14.88Mpps
Packet Buffer	4.1Mbit
Jumbo Frame	10KBytes
Environment	Operating Temperature: 0℃ ~45℃ (32℉~113℉) Storage Temperature: -40℃ ~70℃ (-40℉~158℉) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95% non-condensing

Software Features

L3 Switching Features	• Static Routing • IPv4/IPv6 • Address Resolution Protocol (ARP) • Static ARP
L2 Switching Features	• 8K MAC Address Table • 10K (10000) Jumbo Frame • Flow Control • 802.3x (Full-duplex) • Back-Pressure (Half-duplex) • Spanning Tree • IEEE 802.1D STP • IEEE 802.1w RSTP) • IEEE 802.1s (MSTP)/16 instances • Auto Edge Port • BPDU Filtering • ERPS • Link Aggregation • IEEE 802.3ad LACP • Static Trunk • Max 8 Group • Max 8 Ports/Group • Traffic Load Balancing • Surveillance VLAN • 16 QiQ Mode (Auto/Manual) • Voice VLAN • 16 QiQ Mode (Auto/Manual) • GVRP/ IEEE 802.1ad) • Basic • GARP VLAN Registration Protocol (GVRP) • GVN-Static VLAN • IEEE 802.1Q Tagged-based • 8 groups Protocol-based • 256 MAC-based
Multicast	• Common - 256 Multicast Groups - Immediate Leave - Static/Forbidden Router Port - Static/Forbidden Forward Port • 128 profiles Filtering • IGMP • IGMP Snooping - IGMP v1/v2 - IGMP v3 Basic (BISS) - IGMP v2/v3 Querier • MLD Snooping - MLD v1/v2 • Multicast VLAN Registration (MVR) - IPv4
Quality of Service (QoS)	• Trusted QoS • Queue Scheduling - WRR - WFQ - Strict Priority - Hybrid(WRR+SP or WFQ+SP) • Class of Service - Port-based - 802.1p - IP TOS Precedence - IP DSCP • Rate Limit - Port-based (Ingress/Egress)
Access Control List (ACL)	• ACL Type - L2/L3/L4 - 512 MAC-based - 512 IPv4-based - 512 IPv6-based • PoE Function - Power - Current - Voltage - PoE-Watch Dog • Access Rules - 1024 • AAA Authentication • 8 TACACS+ • 8 RADIUS
Security	• Authentication Manager - IEEE 802.1X - MAC Auth - Web Auth - Guest VLAN - Port-based - MAC-based • Account Manager - Local Authentication - 8 Multiple User Account - Multi-Level Security Manager(Operator) - Password Recovery Procedures • Management Access - Management VLAN - 256Management ACL • SSL - SSLv2 - SSLv3 - TLSv1 • HTTPS • SSH - SSH v1/v2 • Port Security - 256 Dynamic Lock • Storm Control - Broadcast - Unknown Multicast - Unknown Unicast • Spanning Tree - BPDU Guard • Protected Port (Port Isolation) • Black Hole MAC • CPU Defence Engine • DoS Prevention • DHCP Snooping (with Option 82) • Dynamic ARP Inspection • 256 IP Source Guard • IP/MAC/Port Binding (IMPB) • Dynamic VLAN Assignment
IPv6	• IPv6 Host - Auto-Configuration - Static IPv6 Address and Prefix Length - Static IPv6 Default Gateway - IPv6 Neighbor Discovery (ND) - IPv6 Duplicate Address Detection - ICMPv6 • IPv6 Application - HTTP/HTTPS - SSH v1/v2 - SSL - SNMP - TFTP - Syslog - Telnet - DHCPv6
Management	• CLI - 3 sessions Console - 3 sessions Telnet (RFC854) • Web GUI - HTTPS • SNMPv1/v2c/v3 • File Management - Firmware Upgrade/Backup - Dual Images - Configuration Download/Backup - Multiple Configurations • Upload/Download - TFTP (RFC783) - HTTP - SMTP • Time Management - Local Time - SNTP • Port Management - Friendly Port Name (Port Description) - Error Disabled Recovery • Line Management - Console - Telnet (RFC854) - SSH v1/v2 • DHCP - Client • DNS - Client • Software Reset Button
Discovery	• IEEE 1802.3ad • 32 entries / type RMON Management • IEEE 802.1AB Link Layer Discovery Protocol (LLDP) • ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)
Diagnostics	• UDLD • Mirroring - 4 sessions port-based (Many to One) • Syslog (RFC3164) - Local RAM - Local Flash - 8 Remote Server • System Diagnostics - CPU Utilization - Memory Utilization - Port Utilization - Technical Support Log • Port Diagnostics - Cable Test - Fiber Module Status • Network Diagnostics - Ping Test - Traceroute
MIB	• RFC1213 MIB II (System & Interface groups) • RFC2819 RMON I (1,2,3, & 9 groups) • RFC1215 Generic Traps • RFC1493 Bridge • RFC2674 Bridge MIB Extensions • RFC2737 Entity • RFC3635 Ethernet-Like • RFC2863 Interface Group • SNMP-Community-MIB • SNMPv3-MIB