Product Specifications



8x 10G RJ45 Ports Unmanaged Switch (SR-ST1008)

- 8 100M/1000M/2.5G/5G/10G auto-sensing RJ45 ports.
- All ports have wire-speed forwarding capability.
- Plug and play, No configuration required.

Product Description

The SR-ST1008 series is an unmanaged switch with 8x100M/1000M/2.5G/5G/10G auto-sensing RJ45 ports , designed to meet the networking needs of growing businesses.

SR-ST1008 series switches provide different operating modes for applications such as security monitoring, and wireless networking, with good network adaptability.

Features

- Providing 8x100M/1000M/2.5G/5G/10G auto-sensing RJ45 ports.
- All ports support wire-speed forwarding.
- Compliant with IEEE 802.3/802.3u/802.3ab/802.3bz/802.3x/802.3cb standards.
- Supports IEEE 802.3x full-duplex flow control and Backpressure half-duplex flow control.
- Ports supports the self-negotiation function to automatically adjust the transmission method and transmission speed.

试用水印

Hardware Specification

SR-ST1008	
Power Supply	AC 100-240V 50/60Hz
Standards	IEEE 802.3/802.3u/802.3ab/802.3bz/802.3x/802.3cb
Ports	8 100M/1000M/2.5G/5G/10G RJ45 ports
Indicator	8 link/act indicators, 8 10G speed indicators, power input indicator
Network Media (Cable)	100Base-Tx: UTP/STP of Cat. 5 or above (MAX 100 m) 1000Base-T: UTP/STP of Cat. 5e or above (MAX 100m) 2.5GBase-T:UTP/STP of Cat. 5e or above (MAX 100m) 5GBase-T: UTP/STP of Cat. 5e or above (MAX 100m) 10GBase-T: UTP of Cat 6 (MAX 55 m) or STP of Cat 7 (MAX 100m)
Dimensions	271*181.5*44.5 mm
Transfer Method	Store-and-Forward
MAC Address Table	16K
Switching Capacity	160Gbps
Packet Forwarding Rate	119.04Mpps
Packet Buffer	12Mbit
Jumbo Frame	12KBytes
Environment	Operating Temperature: 0℃ ~45℃ (0℉~113℉) Storage Temperature: -40℃ ~70℃ (-40℉ ~158℉) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95% non-condensing