8-Port 10/100/1000Base-T IEEE802.3bt PoE++ 90W to 2-Port 10/100/1000Base-T Uplink Mini Industrial AI Smart Managed PoE++ Ethernet Switch with Voltage Booster System

Features

► Self-developed intelligent management system by E-link, supporting mobile APP and PC Web UI

► One-click LED screen display real-time data dashboard: system current, voltage, internal temperature; Ethernet port link speeds and more

► Intuitive graphical interface under APP/Web for full device status visualization

► Lightweight simplified UI replaces complicated traditional management pages, enabling easy on-site debugging and maintenance even for non-professional operators

► Wide DC input range 9V–54V, built-in voltage boost module

► Compliant with IEEE 802.3af/at/bt, total PoE++ PSE budget up to 90W

► Customizable versions available for Starlink Gen 2 / Gen 3 compatibility

► Flexible PoE power output matching different input voltages:

• 12V input → 60W PoE output

• 24V input → 120W PoE output

• 48V input → 240W PoE output

► 6KV lightning surge protection on all ports

► Wide operating temperature: -40°C ~ +75°C (-40°F ~ 167°F)



Overview

LNK-AIMC010GMP90 is a compact AI smart managed industrial PoE switch independently developed by E-link. Equipped with 4×10/100/1000Base-T RJ45 PoE++ port and 4×10/100/1000Base-T RJ45 PoE+ port + 2×Gigabit uplink RJ45 port, it also supports solar voltage boosting function.

This world-first innovative switch combines the dual advantages of managed and unmanaged switches. Engineers can monitor device status via multiple methods: mobile APP, PC web management interface and LED Display without additional test tools.

Data cover:voltage,current, temperature, Ethernet port status, PoE status,

We innovated this product based on standard switches:

Device function: Scheduled System Reset, PoE Scheduled Restart. The redundant-mode supports auto -recover function. If the destination port of a packet is link-down, it forwards the packet to the other port of the backup pair

Meets IP40, aluminum housing, works stably under harsh industrial temperatures from -40℃ to 75℃.

Equipped with dual redundant power supplies, it keeps Ethernet working stably 24X7.

Application Scenarios:

Intelligent Manufacturing & Automation: data transmission and multi-device interconnection

Power & New Energy: Surveillance communication and cluster networking.


Rail Transit & Tunnel Engineering: Real-time video monitoring and signal transmission.

Oil, Gas & Mining Sites: Stable communication

Smart City & New Infrastructure Deployment

In addition, this product can be used in fields such as autonomous driving, humanoid robots, AI computing, metallurgy, chemical engineering, outdoor research base stations and field weather monitoring.


Application




PoE Standards Parameters							
PoE Standards		**Input(V)**	**Current(A)**	**Output(V)**	**Power(W)**	**PoE Pin**	**Mode**
IEEE802.3af/at/bt	af/at/bt	9-12	5	48V	60	1/2(+),3/6(-); 4/5(+),7/8(-)	ModeA&B
	af/at/bt	19-24	5	48V	120	1/2(+),3/6(-); 4/5(+),7/8(-)	ModeA&B
	af/at/bt	48-54	5	48V	240	1/2(+),3/6(-); 4/5(+),7/8(-)	ModeA&B
Starlink PoE	Gen2	48-56	2.67	56	150	1/2(+),3/6(-); 4/5(+),7/8(-)	
	Gen3	48-56	3.57	56	200	1/2(+),3/6(-); 4/5(+),7/8(-)	




Utilizing hardware IEEE802.3af/at/bt PoE chipset, it automatically powers up PD device with 4 steps (PD Detection -> PoE Classification -> Start Up -> Power ON). Itallocates appropriate power to IEEE802.af/at/bt PoE devices, and no power for non-PoE devices.It ensures high safety for PoE and Non-PoE devices.






E-link App and PC Web











Technical Indexes

Industrial AI Smart Managed PoE++ Switch with Voltage Booster for Solar System		
Access Mode	2*10/100/1000BASE-T RJ45 Uplink to 4*10/100/1000BASE-T RJ45 PSE IEEE802.3af/at/bt + 4*10/100/1000BASE-T RJ45 PSE IEEE802.3af/at	
Ethernet		
Standards:	Standards Compliance IEEE 802.3 Ethernet	
	IEEE 802.3u Fast Ethernet	
	IEEE 802.3ab Gigabit Ethernet	
	IEEE 802.3x Full-Duplex Flow Control	
	IEEE 802.3az Energy Efficient Ethernet (EEE)	
Processing Type	Store-and-Forward	
Forward Filter Rate	14,880pps (10Mbps)	
	148,800pps (100Mbps)	
	1,488,000pps (1000Mbps)	
Packet Buffer Memory	1 Mbit	
Max Packet Length	9K Bytes	
Switching Capacity	20Gbps/non-blocking	
PC (Support MacOS, Windows)		
MacOS Browser:	Microsoft Edge 89+ (Release date: 2021-03-04 or later version) Google Chrome 89+ (Release date: 2021-03-02 or later version) Opera 75+ (Release date: 2021-03-24 or later version)	
Windows Browser:	Microsoft Edge 89+ (Release date: 2021-03-04 or later version) Google Chrome 89+ (Release date: 2021-03-02 or later version) Opera 75+ (Release date: 2021-03-24 or later version)	
Mobile App (Support Android, Not Support iOS)		
Mobile Phone APP(Android)	Support all Android Mobile Phone and Android Tablet	
Mobile iPhone APP(iOS)	Not Support iPhone or iPad	
AI Smart Managed Functions		
Service Board Status	Temperature	
	Voltage	
	Current	
System Status LED	System	
	Power	
	VLAN	
	10M	
RJ45 Port Status	Link Status	
	Current Rate	
	PSE Status	
	PSE Active Pairs	
	PSE Supply Voltage	
	PSE Power Consumption	
	Power Pin Assignment	
	Pair A State	

	Pair B State		
DIP Switch	DIP1	VLAN	
	DIP2	10M	
Restart PoE	Support		
Scheduled Reset	Support		
Port PoE Scheduled Restart	Support		
Interface port			
Ethernet Port	10-Port 10/100/1000BASE-T Ethernet RJ45 interface Auto-negotiation, auto MDI/MDI-X		
	1/3/5/7 port 10/100/1000BASE-T Support IEEE802.3af/at 30W		
	2/4/6/8 port 10/100/1000BASE-T Support IEEE802.3af/at/bt 90W		
	2- port 10/100/1000BASE-T Uplink		
	Cable: Cat 5e or above; Distance: ≤100 meters at 1000M data rate, ≤250 meters at 10M data rate		
PoE (Power over Ethernet)			
Standard	IEEE 802.3af/at/bt PoE++ PSE (af:15.4W,at:30W, bt Type3:60W,bt Type4:90W)		
PoE Power Output	90 Watts max.		
Power Pin Assignment	End-span + Mid-span: 1/2(+), 3/6(-); 4/5(+),7/8(-)		
PoE Budget	Up to 90-watt PoE budget (9-54VDC)		
PoE Power Supply Type	802.3af/at/bt, End-span + Mid-span(If need passive PoE please contact customer service)		
PoE Mode	Compatible with Mode A and Mode B.		
Voltage Booster	DC 9-12V Input	PoE 48V Output, max 60W	DC 19-24V Input	PoE 48V Output, max 120W

	DC 24-36V Input	PoE 48V Output, max 120W	DC 48-54V Input	PoE 48V Output, max 240W
Electrical and Mechanical				
Input Power	9~54V DC, 4-pin terminal block			
Power Consumption	5W Max. (When PoE not used)			
Dimensions (W x D x H)	98 x 67x 64 mm			
Weight	400g			
Casing	Aluminum Case			
Mounting Options	DIN-Rail			
LED Indicators				
SYS	Green LED Blinking: Operating normally			
VLAN	Green Solid On: VLAN On			
	Green LED Off: Off			
10M	Green LED Solid On: Ethernet port link rate is 10M			
	Green LED Off: Ethernet port link rate is 10M/100M/1000M			
NC	NC			
Uplink	Green LED Solid On: Ethernet port link			
	Green LED Slow Blink: Ethernet port link rate is 10M/100M/1000M			
	Green LED Off: Ethernet port no link			
TP1-8 L/A	Green LED Solid On: Ethernet port link			
	Green LED Slow Blink: Ethernet port link rate is 10M/100M/1000M			
	Green LED Off: Ethernet port no link			
TP1-8 PoE	Yellow LED Solid On: Connected PD			
	Yellow LED Off: Not connected PD			
Environmental				
Operating Temperature	-40°C to 75°C (-40°F to 167°F)			
Storage Temperature	-40°C to 85°C (-40°F to 185°F)			
Relative Humidity	5% to 95% non-condensing			
MTBF	> 200,000 hrs			
Regulatory Approvals				
ISO9001, CE, FCC Part 15 Class A, RoHS				
EMI: EN55022:2010+AC: 2011, Class A EN 61000-3-2: 2006+A1: 2009+A2: 2009 EN 61000-3-3: 2013 EN55024: 2010				
EMS: IEC 61000-4-2: 2008 (ESD) IEC 61000-4-3: 2010 (RS) IEC 61000-4-4: 2012 (EFT) IEC 61000-4-5: 2014 (Surge) IEC 61000-4-6: 2013 (CS) IEC 61000-4-8: 2009 (PFMF)				

Ordering Information

Model	Description
LNK-AIMC010GMP90	Industrial AI Smart Managed 2-Port 10/100/1000BASE-T Uplink to4-Port 10/100/1000BASE-T IEEE802.3bt 90W PoE++ and 4-Port 10/100/1000BASE-T IEEE802.3at 30W PoE+ Switch, 9V to 54V DC power input, with Voltage Booster.
Mounting Options	► Default DIN-Rail bracket included.
Power Options	► 240W/5A 48VDC Power Supply. Open Wire for Terminal Block
	► Power Supply is to be purchased separately.